

Package: interactionRCS (via r-universe)

October 11, 2026

Type Package

Title Calculate Estimates in Models with Interaction

Version 0.1.3

Date 2026-09-10

Description A tool to calculate and plot estimates from models in which an interaction between the main predictor and a continuous covariate has been specified. Methods used in the package refer to Harrell Jr FE (2015, ISBN:9783319330396); Durrleman S, Simon R. (1989) <[doi:10.1002/sim.4780080504](https://doi.org/10.1002/sim.4780080504)>; Greenland S. (1995) <[doi:10.1097/00001648-199507000-00005](https://doi.org/10.1097/00001648-199507000-00005)>.

License GPL-3

Depends R (>= 3.6)

Imports graphics, stats, utils, survival, msm, rms, boot, pspline, rlang, stringr

Suggests knitr, rmarkdown, dplyr, mlbench (>= 2.1-11), grDevices, parallel, methods

VignetteBuilder knitr

Roxygen list(markdown = TRUE)

Encoding UTF-8

LazyData true

Config/roxygen2/version 8.1.0

Config/pak/sysreqs cmake make libicu-dev libuv1-dev

Repository <https://gmelloni.r-universe.dev>

Date/Publication 2026-09-11 13:17:49 UTC

RemoteUrl <https://github.com/gmelloni/interactionrcs>

RemoteRef HEAD

RemoteSha 0e822b622ba2759a2cbacce1ae9c80453f2ed8e2

Contents

intEST	2
linLIN	3
loglinHR	5
loglinOR	6
plotINT	8
rscHR	9
rscLIN	10
rscOR	11
umaru	13

Index	15
--------------	-----------

intEST	<i>Returns the estimates of for an unspecified interaction model</i>
--------	--

Description

This function is a dispatcher that generate OR, HR, RR or linear estimates values for a simple or restricted cubic spline interaction model from a logistic, Cox, Poisson or linear regression

Usage

```
intEST(
  var2values,
  model,
  data,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

var2values	numeric vector of var2 points to estimate
model	model of class cph, coxph, lrm, glm or Glm (for glm/Glm, family gaussian, binomial, poisson or quasipoisson). If data is NULL, the function expects to find the data in model\$x.
data	data used in the model. If absent, we will attempt to recover the data from the model. Only used for bootstrap and glm class models

var1	variable that increases by 1 unit from 0
var2	variable to spline. var2values belong to var2
ci	calculate 95% CI?
conf	confidence level. Default 0.95
ci.method	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
ci.boot.method	one of the available bootstrap CI methods from boot.ci . Default percentile
R	number of bootstrap samples if ci.method = "bootstrap". Default 100
parallel	can take values "no", "multicore", "snow" if ci.method = "bootstrap". Default multicore
...	other parameters for boot

Value

if ci = FALSE, a dataframe with initial values and OR/HR/RR/linear estimates , if ci = TRUE a dataframe with 5 columns, initial values, OR/HR/RR/linear estimates, lower CI, upper CI and SE

Examples

```
library(rms)
library(mlbench)
data(SynthDiabetes)
# Set age on a 5-year scale
SynthDiabetes$age <- SynthDiabetes$age/5
# Recode diabetes as 0/1
SynthDiabetes$diabetes <- ifelse(SynthDiabetes$diabetes=="pos" , 1 , 0)
# Logistic model predicting diabetes over BMI, age and glucose
myformula <- diabetes ~ mass + age * rcs( glucose , 3 )
model <- lrm(myformula , data = SynthDiabetes )
intEST( var2values = 20:80
        , model = model , data = SynthDiabetes , var1 ="age", var2="glucose"
        , ci=TRUE , conf = 0.95 , ci.method = "delta")
# Linear model predicting BMI over diabetes, age and glucose
myformula2 <- mass ~ diabetes + age * rcs( glucose , 3 )
model2 <- glm(myformula2 , data = SynthDiabetes , family = "gaussian")
intEST( var2values = 20:80
        , model = model2 , data = SynthDiabetes , var1 ="age", var2="glucose"
        , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

Description

Generate linear estimates for a 1 unit increase in a variable at specified points of another interacting variable in a linear interaction model

Usage

```
linLIN(
  var2values,
  model,
  data,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

var2values	numeric vector of var2 points to estimate
model	model of class <code>rms::Glm</code> or <code>stats::glm</code> family gaussian. If data is <code>NULL</code> , the function expects to find the data in <code>model\$x</code>
data	data used in the model. If absent, it will attempt to recover the data from the model object. Only used for bootstrap CI
var1	variable that increases by 1 unit from 0
var2	variable to spline. var2values belong to var2
ci	calculate 95% CI?
conf	confidence level. Default 0.95
ci.method	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
ci.boot.method	one of the available bootstrap CI methods from boot.ci . Default percentile
R	number of bootstrap samples if ci.method = "bootstrap". Default 100
parallel	can take values "no", "multicore", "snow" if ci.method = "bootstrap". Default multicore
...	other parameters for boot

Value

if `ci = FALSE`, a vector of estimate of `length(var2values)`, if `ci = TRUE` a dataframe with 5 columns, initial values, linear estimates, lower CI, upper CI and SE

Examples

```
library(rms)
library(mlbench)
data(SynthDiabetes)
```

```
# Recode diabetes as 0/1
SynthDiabetes$diabetes <- ifelse(SynthDiabetes$diabetes=="pos" , 1 , 0)
myformula <- glucose ~ mass + diabetes * age
model <- glm(myformula , data = SynthDiabetes ,family=gaussian)
# Show the effect on glucose of being diabetic at age 20 to 80
linLIN( var2values = 20:80
        , model = model , data = SynthDiabetes , var1 ="diabetes", var2="age"
        , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

loglinHR

Linear interaction HR

Description

Generate HR values for a 1 unit increase in a variable at specified points of another interacting variable in a simple Cox interaction model

Usage

```
loglinHR(
  var2values,
  model,
  data,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

var2values	numeric vector of var2 points to estimate
model	model of class coxph or cph. If data is NULL, the function expects to find the data in model\$x
data	data used in the model. If absent, it will attempt to recover the data from the model object. Only used for bootstrap CI
var1	variable that increases by 1 unit from 0
var2	variable to spline. var2values belong to var2
ci	calculate 95% CI?
conf	confidence level. Default 0.95

<code>ci.method</code>	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
<code>ci.boot.method</code>	one of the available bootstrap CI methods from boot.ci . Default percentile
<code>R</code>	number of bootstrap samples if <code>ci.method = "bootstrap"</code> . Default 100
<code>parallel</code>	can take values "no", "multicore", "snow" if <code>ci.method = "bootstrap"</code> . Default multicore
<code>...</code>	other parameters for boot

Value

if `ci = FALSE`, a vector of estimate of length(`var2values`), if `ci = TRUE` a dataframe with 5 columns, initial values, HR, lower CI, upper CI and SE

Examples

```
library(survival)
data(cancer)
myformula <- Surv(time, status) ~ ph.karno + ph.ecog + age*sex
model <- coxph(myformula , data = lung )
loglinHR( var2values = 40:80
          , model = model , data = lung , var1 ="sex", var2="age"
          , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

loglinOR

Linear interaction OR

Description

Generate OR values for a 1 unit increase in a variable at specified points of another interacting variable in a simple logistic interaction model. For Poisson (or quasipoisson) models of class `glm` or `Glm`, rate ratios (RR) are returned instead.

Usage

```
loglinOR(
  var2values,
  model,
  data,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

<code>var2values</code>	numeric vector of var2 points to estimate
<code>model</code>	model of class lrm Glm or glm (family binomial, poisson or quasipoisson). If data is NULL, the function expects to find the data in <code>model\$x</code>
<code>data</code>	data used in the model. If absent, it will attempt to recover the data from the model object. Only used for bootstrap CI
<code>var1</code>	variable that increases by 1 unit from 0
<code>var2</code>	variable to spline. <code>var2values</code> belong to <code>var2</code>
<code>ci</code>	calculate 95% CI?
<code>conf</code>	confidence level. Default 0.95
<code>ci.method</code>	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
<code>ci.boot.method</code>	one of the available bootstrap CI methods from boot.ci . Default percentile
<code>R</code>	number of bootstrap samples if <code>ci.method = "bootstrap"</code> . Default 100
<code>parallel</code>	can take values "no", "multicore", "snow" if <code>ci.method = "bootstrap"</code> . Default multicore
<code>...</code>	other parameters for boot

Value

if `ci = FALSE`, a vector of estimate of `length(var2values)`, if `ci = TRUE` a dataframe with 5 columns, initial values, OR (RR for Poisson models), lower CI, upper CI and SE

Examples

```
library(rms)
library(mlbench)
data(SynthDiabetes)
# Set age on a 5-year scale
SynthDiabetes$age <- SynthDiabetes$age/5
# Recode diabetes as 0/1
SynthDiabetes$diabetes <- ifelse(SynthDiabetes$diabetes=="pos" , 1 , 0)
myformula <- diabetes ~ mass + age * glucose
model <- glm(myformula , data = SynthDiabetes , family = binomial())
loglinOR( var2values = 20:80
          , model = model , data = SynthDiabetes , var1 ="age", var2="glucose"
          , ci=TRUE , conf = 0.95 , ci.method = "delta")
# Poisson model for a count outcome returns rate ratios (RR)
model_pois <- glm(pregnant ~ mass + age * glucose
                  , data = SynthDiabetes , family = poisson())
loglinOR( var2values = 20:80
          , model = model_pois , data = SynthDiabetes , var1 ="age", var2="glucose"
          , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

plotINT

*Plot the result of HR, OR or linear estimates***Description**

Create a spline var2 by 1 unit increase of var1

Usage

```
plotINT(
  x,
  xlab = "",
  main = "",
  log = FALSE,
  ylab = NULL,
  line1 = TRUE,
  linecolor = "dodgerblue",
  cicolor = "darkgray",
  ...
)
```

Arguments

x	data.frame calculated using any of the function of this package
xlab	xlab name
main	plot title
log	if TRUE, plot the estimate in log scale
ylab	ylab name. Default is the estimate column name if log=FALSE otherwise Estimate(log scale)
line1	if TRUE, plot horizontal line on 1 or 0 (if log=TRUE)
linecolor	line color. Default dodgerblue
cicolor	confidence intervals color. Default gray
...	other parameters for plot

Value

simple pspline smoothed splined plot of estimates of 1 unit increase in var1 at var2 values

Examples

```
library(rms)
library(survival)
data(cancer)
myformula <- Surv(time, status) ~ ph.karno + ph.ecog + rcs(age, 3)*sex
model <- cph(myformula , data = lung )
```

```
myHR <- rcsHR( var2values = 40:80
               , model = model , data = lung , var1 ="sex", var2="age"
               , ci=TRUE , conf = 0.95 , ci.method = "delta")
plotINT(myHR , ylab = "HR of male VS female" , xlab = "Age")
```

rscHR

Restricted cubic spline interaction HR for more than 3 knots

Description

Generate HR values in a Cox model for a 1 unit increase in a variable at specified points of another interacting variable splined with rcs(df >= 3)

Usage

```
rcsHR(
  var2values,
  model,
  data = NULL,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

var2values	numeric vector of var2 points to estimate
model	model of class cph or coxph. If data is NULL, the function expects to find the data in model\$x.
data	data used in the model. If absent, we will attempt to recover the data from the model. Only used for bootstrap and coxph models
var1	variable that increases by 1 unit from 0.
var2	variable to spline. var2values belong to var2
ci	calculate 95% CI?
conf	confidence level. Default 0.95
ci.method	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
ci.boot.method	one of the available bootstrap CI methods from boot.ci . Default percentile
R	number of bootstrap samples if ci.method = "bootstrap". Default 100

parallel	can take values "no", "multicore", "snow" if ci.method = "bootstrap". Default multicore
...	other parameters for boot

Value

if ci = FALSE, a dataframe with initial values and HR , if ci = TRUE a dataframe with 5 columns, initial values, HR, lower CI, upper CI and SE

Examples

```
library(survival)
library(rms)
data(cancer)
myformula <- Surv(time, status) ~ ph.karno + ph.ecog + rcs(age,4)*sex
model <- cph(myformula , data = lung )
rcsHR( var2values = 40:80
      , model = model , data = lung , var1 ="sex", var2="age"
      , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

rscLIN	<i>Restricted cubic spline interaction linear estimates for more than 3 knots</i>
--------	---

Description

Generate estimates in a linear model for a 1 unit increase in a variable at specified points of another interacting variable splined with rcs(df >= 3)

Usage

```
rscLIN(
  var2values,
  model,
  data = NULL,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

var2values	numeric vector of var2 points to estimate
model	model of class rms::Glm or stats::glm family gaussian. If data is NULL, the function expects to find the data in model\$x.
data	data used in the model. If absent, we will attempt to recover the data from the model. Only used for bootstrap
var1	variable that increases by 1 unit from 0
var2	variable to spline. var2values belong to var2
ci	calculate 95% CI?
conf	confidence level. Default 0.95
ci.method	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
ci.boot.method	one of the available bootstrap CI methods from boot.ci . Default percentile
R	number of bootstrap samples if ci.method = "bootstrap". Default 100
parallel	can take values "no", "multicore", "snow" if ci.method = "bootstrap". Default multicore
...	other parameters for boot

Value

if ci = FALSE, a dataframe with initial values and linear estimates , if ci = TRUE a dataframe with 5 columns, initial values, linear estimates, lower CI, upper CI and SE

Examples

```
library(rms)
library(mlbench)
data(SynthDiabetes)
# Recode diabetes as 0/1
SynthDiabetes$diabetes <- ifelse(SynthDiabetes$diabetes=="pos" , 1 , 0)
myformula <- glucose ~ mass + diabetes * rcs(age, 4)
model <- glm(myformula , data = SynthDiabetes , family="gaussian")
# Show the effect on glucose of being diabetic at age 20 to 80
rcsLIN( var2values = 20:80
        , model = model , data = SynthDiabetes , var1 ="diabetes", var2="age"
        , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

Description

Generate OR values in a logistic model for a 1 unit increase in a variable at specified points of another interacting variable splined with rcs(df >= 3). For Poisson (or quasipoisson) models of class glm or Glm, rate ratios (RR) are returned instead.

Usage

```
rcsOR(
  var2values,
  model,
  data = NULL,
  var1,
  var2,
  ci = TRUE,
  conf = 0.95,
  ci.method = "delta",
  ci.boot.method = "perc",
  R = 100,
  parallel = "multicore",
  ...
)
```

Arguments

<code>var2values</code>	numeric vector of <code>var2</code> points to estimate
<code>model</code>	model of class <code>lrm</code> , <code>Glm</code> or <code>glm</code> (family binomial, poisson or quasipoisson). If <code>data</code> is <code>NULL</code> , the function expects to find the data in <code>model\$x</code> .
<code>data</code>	data used in the model. If absent, we will attempt to recover the data from the model. Only used for bootstrap and <code>glm</code> class models
<code>var1</code>	variable that increases by 1 unit from 0
<code>var2</code>	variable to spline. <code>var2values</code> belong to <code>var2</code>
<code>ci</code>	calculate 95% CI?
<code>conf</code>	confidence level. Default 0.95
<code>ci.method</code>	confidence interval method. "delta" performs delta method. "bootstrap" performs bootstrapped CI (slower)
<code>ci.boot.method</code>	one of the available bootstrap CI methods from boot.ci . Default percentile
<code>R</code>	number of bootstrap samples if <code>ci.method = "bootstrap"</code> . Default 100
<code>parallel</code>	can take values "no", "multicore", "snow" if <code>ci.method = "bootstrap"</code> . Default multicore
<code>...</code>	other parameters for boot

Value

if `ci = FALSE`, a dataframe with initial values and OR (RR for Poisson models)

Examples

```
library(rms)
library(mlbench)
data(SynthDiabetes)
# Set age on a 5-year scale
SynthDiabetes$age <- SynthDiabetes$age/5
```

```
# Recode diabetes as 0/1
SynthDiabetes$diabetes <- ifelse(SynthDiabetes$diabetes=="pos" , 1 , 0)
myformula <- diabetes ~ mass + age * rcs( glucose , 4 )
model <- glm(myformula , data = SynthDiabetes , family = "binomial")
rcsOR( var2values = 20:80
      , model = model , data = SynthDiabetes , var1 ="age", var2="glucose"
      , ci=TRUE , conf = 0.95 , ci.method = "delta")
# Poisson model for a count outcome returns rate ratios (RR)
model_pois <- glm(pregnant ~ mass + age * rcs( glucose , 4 )
                  , data = SynthDiabetes , family = poisson())
rcsOR( var2values = 20:80
      , model = model_pois , data = SynthDiabetes , var1 ="age", var2="glucose"
      , ci=TRUE , conf = 0.95 , ci.method = "delta")
```

umaru

UMARU IMPACT Study data

Description

A subset of data from the University of Massachusetts Aids Research Unit (UMARU) IMPACT study.

Usage

umaru

Format

A data frame with 575 rows and 10 variables

X observation count

id identification code

age Age in years

beckscore Beck Depression Score at admission

ndrugtx Number of prior drug treatments

treat treat

site site

los los

time time to event

censor censor event

heroin heroin use at admission

cocaine cocaine use at admission

drugtx Prior Drug treatment, yes/no

ivdrug Prior IV drug treatment

nonwhite 1 if non white, 0 otherwise

Source

https://ftp.idu.ac.id/wp-content/uploads/ebook/ip/REGRESI%20LOGISTIK/epdf.pub_applied-logistic-regression.pdf

Index

* **datasets**

umaru, [13](#)

boot.ci, [3](#), [4](#), [6](#), [7](#), [9](#), [11](#), [12](#)

intEST, [2](#)

linLIN, [3](#)

loglinHR, [5](#)

loglinOR, [6](#)

plotINT, [8](#)

rcsHR, [9](#)

rcsLIN, [10](#)

rcsOR, [11](#)

umaru, [13](#)